





WWW.CHIPPC.COM



Processor / Core Logic	<ul style="list-style-type: none"> • Intel® Pentium® Silver N5000 processor (14nm, 1.1GHz, DDR4-2400MHz, 4MB Smart Cache, TDP: 6W) • Intel® Celeron® N4100 processor (14nm, 1.1GHz, DDR4-2400MHz, 4MB Smart Cache, TDP: 6W) • Intel® Celeron® N4000 processor (14nm, 1.1GHz, DDR4-2400MHz, 4MB Smart Cache, TDP: 6W)
Display	<ul style="list-style-type: none"> • 14.0" (35.56cm) HD (1366x768) / FHD (1920x1080) 16:9 panel, 3.6mm
Memory	<ul style="list-style-type: none"> • Dual channel DDR4 • Two 260 pins SODIMM sockets, support DDR4 2400MHz (Real operation frequency depends on processor) • Expandable memory up to 8GB, depends on 4GB / 8GB SODIMM module
Video Controller	<ul style="list-style-type: none"> • Intel® UHD Graphics 605 (N5000 CPU) <ul style="list-style-type: none"> - Dynamic frequency - Intel Dynamic Video Memory Technology - Microsoft DirectX® 12 compatible • Intel® UHD Graphics 600 (N4100, N4000 CPU) <ul style="list-style-type: none"> - Dynamic frequency - Intel Dynamic Video Memory Technology - Microsoft DirectX® 12 compatible
Storage	<ul style="list-style-type: none"> • One changeable 2.5" 7.0mm(H) HDD / SSD, SATA interface • (Factory Option) M.2 SSD 2280, SATA3 interface • (Factory Option) eMMC 32GB / 64GB
Audio	<ul style="list-style-type: none"> • High Definition Audio • Built in array microphone • Built in two speakers
Keyboard and Pointing Device	<ul style="list-style-type: none"> • Multi languages A4 size isolated keyboard • Built in touch pad with Microsoft PTP multi-gesture and scrolling function
I/O ports	<ul style="list-style-type: none"> • 1 x USB 2.0 port • 1 x USB 3.0 (USB3.1 Gen 1) port (Type A) • 1 x USB 3.0 (USB3.1 Gen 1) port (Type C) • 1 x external VGA port • 1 x HDMI output port (with HDCP) • 1 x Headphone jack • 1 x Microphone jack • 1 x RJ-45 LAN port • 1 x DC-in jack 
Card Reader	<ul style="list-style-type: none"> • 6-in-1 Push-Push Card reader <ul style="list-style-type: none"> - MMC / RSMHC - SD / mini SD / SDHC / SDXC
Slot	<ul style="list-style-type: none"> • Two M.2 Card slots <ul style="list-style-type: none"> - 1st for WLAN Combo M.2 2230 Card with PCIE / USB / CNVi interface (E key) - 2nd for M.2 SSD 2280 Card with SATA interface (B key)
Communication	<ul style="list-style-type: none"> • Built in 10/100/1000Mb Base-TX Ethernet LAN • (Factory option) Intel®Dual Band Wireless-AC 9260 2x2 AC +BT M.2 2230 (Thunder Peak 2) • (Factory option) Intel®Dual Band Wireless-AC 9560 2x2 AC +BT M.2 2230 (Jefferson Peak 2) • (Factory option) Intel®Dual Band Wireless-AC 9462 1x1 AC +BT M.2 2230 (Jefferson Peak 1) • 1.0M HD video camera
Power Supply	<ul style="list-style-type: none"> • Full Range AC adapter, AC in 100~240V, 50~60Hz, DC output 19V 2.1A, 40W • Removable 4 cells Smart Lithium-Ion battery pack, 32WH • (Factory option) Removable 4 cells Smart Lithium-Ion battery pack, 44WH • Battery life: 385 minutes (with 32WH battery) • Battery life: 530 minutes (with 44WH battery)
Security	<ul style="list-style-type: none"> • Security (Kensington® Type) Lock Slot • Intel® PTT for system without Hardware TPM
Others design	<ul style="list-style-type: none"> • Shipping mode • FlexiCharger • Microsoft Cortana with Voice Technology • Fan Silent Mode
O.S. Support	<ul style="list-style-type: none"> • Windows® 10 RS3 (64 bits)
Certificate	<ul style="list-style-type: none"> • Windows® 10 RS3 (64-bit) Logo • HDMI™ Logo
Dimension	<ul style="list-style-type: none"> • 340(W) x 243.5(D) x 22.2 (H)mm (Height excluded battery area)
Weight	<ul style="list-style-type: none"> • 1.8kg, including Barebone and 32WH Battery

Remark:

*Battery life may vary depending on applications and configuration.

*Weight tolerance is +/- 5%.

*The content is subject to change without notices. Other brand and product names are trademarks and/or register trademarks of their respective companies.